Ø 006

MAR 0 7 2007

Page 1 of 1

BEST AVAILABLE COPY

Electrooptics device and mfg method, electronic instrument

Publication number: CN1484478

Publication date:

esp@cenet document view

2004-03-24

Inventor:

REIICHI NOSAWA (JP)

Applicant:

SEIKO EPSON CORP (JP)

Classification:

- International:

H05B33/22; H01L27/32; H01L29/786; H01L51/30; H01L51/50; H05B33/10; H05B33/26; H01L51/40; H05B33/22; H01L27/28; H01L29/66; H01L51/05; H01L51/50; H05B33/10; H05B33/26; (IPC1-7):

H05B33/14; H05B33/10

- European:

H01L27/32M2; H01L51/00M2B4; H05B33/26

Application number: CN20031054008 20030813 Priority number(s): JP20020253489 20020830 Also published as:


团 US 7122954 (B2) 团 US 2004056588 (A1)

J P2004095290 (A)

Report a data error here

Abstract not available for CN1484478
Abstract of corresponding document: US2004056588

An electro-optical device and a method of manufacturing the same capable of suppressing an influence due to an irregularity of a switching element or a wiring line on a functional element is provided. An organic EL apparatus includes on a substrate P an organic EL device 200, a wiring for supplying a power to the organic EL device 200, and a switching element 143. An insulating layer 100 is formed on the substrate P, and a concave part is formed in the insulating layer 100 to dispose the switching element 143.



Data supplied from the esp@cenet database - Worldwide